

Nomex Fiber Packing

Code: KXTP304



Description

Nomex Fiber Packing braided from high quality Dupont Spun nomex yarns with PTFE impregnated and lubricant additive, high cross-sectional density and structural strength, good sliding characteristic, gentle on shaft. Compared to kevlar, not hurt shaft, good idea for food industries.



Nomex Fiber Packing

Item no.: KXTP304

- * Good sliding characteristic, gentle on shaft surfaces.
- * Not hurt shaft, also ideal for food industries.
- * Clean packing and easy-to-install packing.

Item no.: KXTP304

Typical Application

- * This is a universal packing which can be used for pumps in all types of industry.
- * Designed specially for pumps, agitators, mixers, kneaders, refiners, etc.
- * Excellently suitable for standardization in entire industrial sectors.

Technical Data

Material		Dupont Aramid Fiber (with or without PTFE impregnated)
Temperature Range		-150 up to +280 oC
Process	Rotating	25 bar
	Reciprocating	50 bar
	Static	100 bar
Shaft Speed		20 m/s (Rotating)
PH		1~13
Density		Appr. 1.3 g/cm3

Copyright © 2014-2015

Ningbo Kaxite Sealing Materials Co., Ltd.

No.134,Huancheng North Road,Jiangbei District,

Ningbo City,Zhejiang Province,China (Zip:315020)

Website:<http://www.seal-china.com> E-mail:sales@seal-china.com